





BASE METAL	15 YIL GARANTİ	ÇİNKO KAPLAMA Z225 GR/MQ
	KOLAY UYGULAMA	DX51 + DX53
YÜZEY A 35μm K2 SURFACE	UV DAYANIKLI	35μm K2 YÜZEY
	ÇİZİLMELERE DAYANIKLI	
YÜZEY B POLYESTER 25μm		POLYESTER 25μm





	MAVIS	BOYALI SAC
BASE METAL	DX51	DX51
ÇİNKO KAPLAMA	225 gr/mq	100 gr/mq
YÜZEY A	35 μm K2	25 μm POLYESTER
YÜZEY B	25 μm polyester	17 μm POLYESTER/PRIMER
SURFACE PENCIL HARDNESS	н	HB to F
CRACK FORMATION DURING BENDIG	≤ 2T free of cracks	≤ 3T free of cracks
ADHESION AFTER BENDING	≤ 1T peel adhesion	≤ 2T peel adhesion
SALT SPRAY TEST	500 H	360 H
UV DAYANIM	RUV4	RUV2
KOROZYON DAYANIM KATEGORİSİ	RC4	RC3
YÜZEY GÖRÜNÜM	PÜRÜZSÜZ	PÜRÜZSÜZ
GARANTİ	15 YIL	GARANTİ YOK







## **EASE OF INSTALLATION**

In order to simplify the work of the installers, Mavis is divided into two products; the line with base metal DX51D is harder and is recommended for gutter prodoction, while the line with base metal DX53D is softer and malleable, ideal for roofing with double lock standing seam.



## **ECOLOGICAL AND RECYCLABLE**

Mavis is atoxic and 100% recyclable





More weatherproof than normal surfaces. More long-lasting.



## SCRATCH-RESISTANT

Scratch-resistant to facilitate operator's activity and to achieve a more aesthetic result for his customer.

